



TECHNICAL DATA SHEET

Version 2 01/02/2017

FULLABOND 3135A PB

Type of Adhesive FULLABOND 3135A PB has been developed for gluing paper and

> cardboard with difficult to bond surfaces. It is suitable for bonding of UVcoated materials and shows good adhesion on various foils. It is also suitable for case sealing as well as window gluing in the packaging

industry.

Product Benefits Bonds to difficult surfaces, UV-Coated materials, various foils, it can be

used at -40°C, short open time and short compression time.

Typical Applications FULLABOND 3135A PB is especially used in the food industry as well

> as for deep freezing goods. It has good machinability, elastic bonding, excellent adhesion on coated surfaces and foils (e.g. PVC, PS, PET, acetate, aluminum, etc). It requires a short open time with very short

setting/compression time

Typical Properties

Raw material base	Ethylene vinyl acetate emulsion
Viscosity (Spindle 4, 20RPM, 20°C)	3,000 - 3,850 cP
рН	ca. 4.0
Specific Gravity	ca. 1.1
Solids (%)	ca. 57
Application Type	Wheel, contact nozzles, disc or roller
Storage	Store out of direct sunlight between 10 and 35 °C. Protect from freezing at all times.
Shelf Life	6 months
Clean-Up	Clean up the adhesive while it's wet with warm soapy water
Safety Advice	Please refer to the SDS

Made in Australia

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a quarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.

Australia Tel: +61 1800 423 855 customer.service@hbfuller.com China & Hong Kong Tel: +86 20 82068291 cs.china@hbfuller.com

Indonesia Tel: +62-21-5307232/33

Tel: +82 2 786 8296 cskorea@hbfuller.com Malaysia Tel: +603 3345 5200 New Zealand Tel: +64 800 555 072 customer.service@hbfuller.com

Korea

Philippines Tel: +63 2 5194073 Taiwan Tel: +886 2 26033385 Thailand Tel: +66 2 3757442 Vietnam Tel: +84 8 22225588

