

TECHNICAL DATA SHEET



Version 1 01/03/17

FULLABOND M 100LV

| Type of Adhesive | Fullabond M100LV is a lower viscosity, fast set carton sealing adhesive. It is primarily designed for the formation of cartons through medium to high-speed equipment where standard corrugated board is used. |
|----------------------|---|
| Product Benefits | Fullabond M100LV has high initial tack, good grab and a very fast set speed. Good flow through a cascade system with little to no skinning. |
| Typical Applications | Case sealing, Cores for tissue or towel, etc. |

Typical Properties

| Raw material base | Synthetic polymer emulsion |
|-------------------------|---|
| Appearance | White |
| Viscosity | 1,800 – 2,000 cps |
| Solids (%) | 48 – 52 |
| Specific Gravity | Circa 1.06 |
| Application information | Fullabond M100LV is designed to be applied by nozzle or wheel and runs on most types of carton sealing and core winding equipment. |
| Limitations | Check machine and material compatibility prior to commercial use. |
| Storage | Product should be stored in the original container out of direct sunlight between 5°C and 30°C and protected from freezing. Rotate stock using oldest batches first. Close containers air tight after use. |
| Shelf life | 6 months |
| Clean-up | Clean up adhesive while wet with warm water. |
| Safety Advice | Please refer to the SDS for safety advice. |

Made in Australia

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including putpose), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.

Australia Tel: +61 1800 423 855 customer.service@hbfuller.com China & Hong Kong Tel: +86 20 82068291 cs.china@hbfuller.com Indonesia Tel: +62-21-5307232/33 Korea Tel: +82 2 786 8296 cskorea@hbfuller.com Malaysia Tel: +603 3345 5200 New Zealand Tel: +64 800 555 072 customer.service@hbfuller.com

 Philippines

 Tel: +63 2 5194073

 Taiwan

 Tel: +886 2 26033385

 Thailand

 Tel: +66 2 3757442

 Vietnam

 Tel: +84 8 22225588

