



FULLAMELT 2220

- Type of Adhesive** FULLAMELT 2220 has been formulated to meet industry requirements for a medium setting, light coloured pressure sensitive hot melt adhesive. FULLAMELT 2220 will provide excellent bonding to difficult substrates including short fibre recycled board with re-pulped content.
- Product Benefits** FULLAMELT 2220 is superior to standard hot melt adhesives and exhibits the improved features of low odour, excellent thermal stability and very good machining properties. FULLAMELT 2220 provides strong bonding properties over an extensive range of storage and handling temperatures.
- Typical Applications** FULLAMELT 2220 is designed to secure substrates over wide range of packaging operations including indirect food contact applications.

Typical Properties

Raw material base	Synthetic polymer based hot melt
Colour	Pale clear
Viscosity @ 177°C (Brookfield)	Circa 3,200 - 4,500 cP
Ring & Ball Softening Point	Circa 85 °C
Application Method	Nozzle, wheel, reservoir pump etc.
Application Temperature	170 °C - 190 °C
Shelf Life	12 months
Safety Advice	Please refer to SDS

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.

Australia
Tel: +61 1800 423 855
customer.service@hbfuller.com
China & Hong Kong
Tel: +86 20 82068291
cs.china@hbfuller.com
Indonesia
Tel: +62-21-5307232/33

Korea
Tel: +82 2 786 8296
cskorea@hbfuller.com
Malaysia
Tel: +603 3345 5200
New Zealand
Tel: +64 800 555 072
customer.service@hbfuller.com

Philippines
Tel: +63 2 5194073
Taiwan
Tel: +886 2 26033385
Thailand
Tel: +66 2 3757442
Vietnam
Tel: +84 8 2225588

